



PART.	MOD. 149	MOD. 150
1	OM14901	OM14901
2	-	IE149402
4	OM14904	OM14904
5	OM14905	OM14905
6	6206 2RS	6206 2RS
7	OM14907	OM14907
8	OM14908	OM14908
9	OM14909	OM14909
10	5739 1020	5739 1020
11	5739 616	5739 616
12	OM14912	OM14912
13	5933 1225	5933 1225
14	OM14914	OM14914
15	OM15226	OM15226
16	OM14916	OM14916
17	OM14917	OM14917
18	OM14918	OM14918
19	OM14919	OM14919
20	OM14920	OM14920
21	OM14921	OM14921
22	5739 1255	5739 1255
23	5931 830	5931 830
24	OM14924	OM14924
25	OM14925	OM14925
26	OM14926	OM14926
27	AS80105	AS80105
28	LS80105	LS80105
29	AXK80105	AXK80105
30	OM15206	-
31	OM15207	OM15207
32	OM15208	OM15208
33	OM15225	-
34	OM15215	-
35	OM15218	-
36	OM15213	-
37	OM15414	-
38	OM15212	-
39	OM14939	-
40	OM15217	-
41	OM15218	-
42	OM15219	-
43	DIN471 15	-
44	OM15221	-
45	OM15220	-
46	5931 1280	-
47	5931 1085	-
48	5931 1045	5931 1045
49	5931 816	5931 816
50	ETI.07	ETI.07
51	OM14951	OM14951
53	OM15227	OM15227
54	5923 610	5923 610
55	-	OM15332
56	-	OM15333
57	-	OM15335
58	-	OM15337
59	-	5931 620
60	-	OM16016
61	-	OM15339
62	-	OM15340
63	-	OM15341
64	-	OM15342
65	-	OM15343
66	-	OM15344
67	-	OM15345
68	-	5931 840

**PIEGAFERRI ELETTRICO SEMIAUTOMATICO
SEMI-AUTOMATIC ELECTRIC ROD BENDING UNIT**

**CURVAFERRI ELETTRICO SEMIAUTOMATICO
SEMI-AUTOMATIC ELECTRIC ROD BENDING UNIT**

MOD	IN ACCIAIO R = 45 KG. MM ² OF STEEL R = 45 KG. MM ²	A FREDDO COLD	A CALDO HOT	Kg. Kg.	mm		
					T	U	H
149	mm	100 x 5	100 x 8	132	70	50	118
	mm	18	24				
	mm	16	22				

MOD	IN ACCIAIO R = 45 KG. MM ² OF STEEL R = 45 KG. MM ²	A FREDDO COLD	A CALDO HOT	Kg. Kg.	mm		
					T	U	H
150	mm	50 x 80	80 x 80	101	70	50	108
	mm	12	12				
	mm	12	12				

Morsa ad eccentrico a 4 posizioni. Motoriduttore HP 1,50 trifase 220/380 V. 50/60 Hz. Applicando l'articolo 158 si può trasformare in curvaferrì mod. 150 con comandi a bassa tensione.

Motoriduttore HP 1,50 trifase 220/380 V. 50/60 Hz. Applicando l'articolo 157 si può trasformare in mod. 149. Con comandi a bassa tensione.

4 position eccentric vice. Gearbox with HP 1,50 3-phase 220-380 V. 50/60 Hz. The unit can be charged into mod. 150 by fitting art. 158 with low-tension controls.

Gearbox with HP 1,50 3-phase 220-380 V. 50/60 Hz. The unit can be charged into mod. 149 by fitting art. 157. With low-tension controls.